

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
6 May 2005 (06.05.2005)

PCT

(10) International Publication Number
WO 2005/041345 A1

(51) International Patent Classification: **H01P 1/203**

Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148
Torino (IT).

(21) International Application Number:
PCT/EP2003/010825

(74) Agents: GIANNESI, Pier, Giovanni et al.; Pirelli & C.
S.p.A., Viale Sarca, 222, I-20126 Milano (IT).

(22) International Filing Date:
30 September 2003 (30.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicants (for all designated States except US): TELE-
COM ITALIA S.P.A. [IT/IT]; Piazza degli Affari, 2,
I-20123 Milano (IT). PIRELLI & C. S.P.A. [IT/IT]; Via
G. Negri, 10, I-20123 Milano (IT).

(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): ACCATINO, Lu-
ciano [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli,
274, I-10148 Torino (IT). BERTIN, Giorgio [IT/IT];


(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: DUAL MODE FILTER BASED ON SMOOTHED CONTOUR RESONATORS



(57) Abstract: A planar filter comprising a planar resonator (1, 20) including a conductive region (2, 21) having smoothed contours and supporting a first resonating mode propagating along a first conductive path (3) and a second resonating mode propagating along a second conductive path (4), perpendicular to the first conductive path. The planar filter also comprises a conductor-free region (5) made in the conductive region (2, 21) and having smoothed contours. The conductor-free region (5) is disposed along a region axis (6) forming an angle θ with respect to the first conductive path (3). The conductor-free region (5) causes a perturbation of the symmetry of the planar resonator (1, 20) resulting in a frequency shift of the first and the second resonating mode and their mutual coupling.





SE, SI, SK, TR). OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW. ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG,

ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG) of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.